



Marine

SAFETY DATA SHEET

Product name: GulfSea Gear Oil 68, 100, 150, 220, 320 460, 680 Page: 1/9
Supersedes date: 2019-11-18 Revision: 2019-11-18
Product No.: SDS-ID: HK-EN/1.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: GulfSea Gear Oil 68, 100, 150, 220, 320 460, 680

Container size: -

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application: Gear oil.

1.3. Details of the supplier of the safety data sheet

Supplier: Gulf Oil Marine Ltd.
28/F, Unit 2802 Citicorp Centre,
18 Whitfield Road, Causeway Bay,
Hong Kong
Tel: +852 36930568
Fax: +852 37489960
sds@gulf-marine.com

1.4. Emergency telephone number

Emergency telephone: +852 36930568

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS: Not classified.

2.2. Label elements

Safety data sheet available on request.

2.3. Other hazards

Other: Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema, skin cracking and oil acne. The harmful effects may increase in used oil. The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Mineral oil and additives.

Only classified substances above threshold limits or substances with an exposure limit are shown.



Marine

SAFETY DATA SHEET

Product name: GulfSea Gear Oil 68, 100, 150, 220, 320 460, 680 Page: 2/9
Supersedes date: 2019-11-18 Revision: 2019-11-18
Product No.: SDS-ID: HK-EN/1.0

GHS:

%:	CAS-No.:	EC No.:	REACH Reg. No:	Chemical name:	Hazard classification:	Notes:
0.1-0.5	1474044-79-5	939-717-7	-	Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	Skin Irrit. 2;H315 Eye Irrit. 2;H319 Skin Sens. 1;H317	

Notes:

The mineral oil contained may be described by one or more of the following:
EC No. 265-157-1, Distillates (petroleum), hydrotreated heavy paraffinic; EC No. 265-169-7, Distillates (petroleum), solvent-dewaxed heavy paraffinic; EC No. 265-158-7, Distillates (petroleum), hydrotreated light paraffinic; EC No. 265-159-2, Distillates (petroleum), solvent-dewaxed light paraffinic.

Reference: The full text for all hazard statements is displayed in section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation: Move into fresh air and keep at rest. In case of persistent throat irritation or coughing: Seek medical attention and bring these instructions.

Skin contact: Remove contaminated clothing. Rinse skin immediately. Thoroughly rub with liquid soap and wash with lukewarm water. Get medical attention if any discomfort continues.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

Ingestion: DO NOT induce vomiting. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects: See section 11 for more detailed information on health effects and symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: If there is any suspicion of aspiration into the lungs either directly or as a result of vomiting, obtain medical advice.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Extinguish with foam, carbon dioxide, dry powder or water fog. Cool containers exposed to heat with water spray and remove container, if no risk is involved.
Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards: When heated and in case of fire, harmful vapours/gases may be formed. Fire in closed areas should only be extinguished by trained personnel.

5.3. Advice for firefighters

Protective equipment for fire-fighters: Wear suitable respiratory protective equipment.



Marine

SAFETY DATA SHEET

Product name: GulfSea Gear Oil 68, 100, 150, 220, 320 460, 680 Page: 3/9
Supersedes date: 2019-11-18 Revision: 2019-11-18
Product No.: SDS-ID: HK-EN/1.0

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark the spillage. Avoid inhalation of oil mist and contact with skin and eyes. Keep public away from danger area. In case of spills, beware of slippery floors and surfaces.

Protective equipment: Wear necessary protective equipment.

6.2. Environmental precautions

Environmental precautions: Avoid discharge into drains. Contact local authorities in case of spillage to drain/aquatic environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material.

6.4. Reference to other sections

Reference: For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice: Observe good chemical hygiene practices. Avoid inhalation of oil mist and contact with skin and eyes. Avoid prolonged and repeated contact with oil, particularly used oil. Wash hands before breaks and before smoking, eating or drinking.

Technical measures: Use work methods which minimise oil mist production. Do not smoke or use open fire or other sources of ignition.

Technical precautions: When working with heated oil, mechanical ventilation may be required.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures for safe storage: Store in tightly closed original container in a well-ventilated place.

Storage conditions: Keep at a temperature not exceeding 45°C.

7.3. Specific end use(s)

Specific use(s): Lubricant.



Marine

SAFETY DATA SHEET

Product name: GulfSea Gear Oil 68, 100, 150, 220, 320 460, 680 Page: 4/9
Supersedes date: 2019-11-18 Revision: 2019-11-18
Product No.: SDS-ID: HK-EN/1.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

<u>CAS-No.:</u>	<u>Chemical name:</u>	<u>As:</u>	<u>Exposure limits:</u>	<u>Type:</u>	<u>Notes:</u>	<u>References:</u>
-	Oil mist, -mineral	-	5 mg/m ³	PEL (Long Term)	-	
		-	10 mg/m ³	PEL (Short Term)	-	

8.2. Exposure controls

<u>Engineering measures:</u>	Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapours and oil mist.
<u>Respiratory equipment:</u>	No specific recommendations.
<u>Hand protection:</u>	Gloves (synthetic rubber, neoprene)
<u>Eye protection:</u>	Wear approved, tight fitting safety glasses where splashing is probable.
<u>Skin protection:</u>	Wear appropriate clothing to prevent repeated or prolonged skin contact.
<u>Hygiene measures:</u>	Wash hands after handling. Observe good chemical hygiene practices. Wash contaminated clothing before reuse. When using do not eat, drink or smoke. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.



Marine

SAFETY DATA SHEET

Product name: GulfSea Gear Oil 68, 100, 150, 220, 320 460, 680 Page: 5/9
Supersedes date: 2019-11-18 Revision: 2019-11-18
Product No.: SDS-ID: HK-EN/1.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance: Viscous liquid.
Colour: Yellow.
Odour: Characteristic.
Odour threshold: Not available.
pH: Not applicable.
Melting point / freezing point: Not available.
Boiling point: Not available.
Flash point: 224-255°C
ASTM D 92
Evaporation rate: Not available.
Flammability (solid, gas): Not applicable.
Explosion limits: Not available.
Vapour pressure: Not available.
Vapour density: Not available.
Relative density: ~ 0.9
Solubility: Soluble in: Organic solvents.
Partition coefficient (n-octanol/water): Not available.
Auto-ignition temperature (°C): Not available.
Decomposition temperature (°C): Not available.
Viscosity: 68.2 – 682.4 mm²/s (40°C)
Explosive properties: Not available.
Oxidising properties: Not available.

9.2. Other information

Other data: Not available.



Marine

SAFETY DATA SHEET

Product name: GulfSea Gear Oil 68, 100, 150, 220, 320 460, 680 Page: 6/9
Supersedes date: 2019-11-18 Revision: 2019-11-18
Product No.: SDS-ID: HK-EN/1.0

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity: Not reactive.

10.2. Chemical stability

Stability: Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: None known.

10.4. Conditions to avoid

Conditions/materials to avoid: Heat, sparks, flames.

10.5. Incompatible materials

Incompatible materials: Strong oxidizing substances.

10.6. Hazardous decomposition products

Hazardous decomposition products: None under normal conditions. Hazardous polymerisation will not occur.



Marine

SAFETY DATA SHEET

Product name: GulfSea Gear Oil 68, 100, 150, 220, 320 460, 680 Page: 7/9
Supersedes date: 2019-11-18 Revision: 2019-11-18
Product No.: SDS-ID: HK-EN/1.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute Toxicity (Oral): Based on available data, the classification criteria are not met.

Acute Toxicity (Dermal): Based on available data, the classification criteria are not met.

Acute Toxicity (Inhalation): Based on available data, the classification criteria are not met.

Skin Corrosion/Irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive Toxicity: Based on available data, the classification criteria are not met.

STOT - Single exposure: Based on available data, the classification criteria are not met.

STOT - Repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Inhalation: Inhalation of oil mist or vapours formed during heating of the product may irritate the respiratory system and provoke throat irritation and coughing.

Skin contact: Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis.

Eye contact: May cause temporary eye irritation.

Ingestion: Low order of acute toxicity, but aspiration following ingestion and vomiting may cause severe and potentially fatal chemical pneumonitis.

Specific effects: The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact. Used oil may contain harmful contaminants.



Marine

SAFETY DATA SHEET

Product name: GulfSea Gear Oil 68, 100, 150, 220, 320 460, 680 Page: 8/9
Supersedes date: 2019-11-18 Revision: 2019-11-18
Product No.: SDS-ID: HK-EN/1.0

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity: Not classified as dangerous to the environment.

12.2. Persistence and degradability

Degradability: Potentially degradable, but will persist in the environment for long periods.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

12.4. Mobility in soil

Mobility: Spillages may penetrate the soil causing ground water contamination.

12.5. Results of PBT and vPvB assessment

PBT/vPvB: Not known.

12.6. Other adverse effects

Other adverse effects: Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

Contaminated packaging: Disposal through approved facilities is recommended.

SECTION 14: TRANSPORT INFORMATION

The product is not regulated as dangerous goods under IMDG Code, IATA-DGR and ADR/RID.

14.1. UN number

UN-No: Not regulated.

14.2. UN proper shipping name

Proper Shipping Name: Not regulated.

14.3. Transport hazard class(es)

Class: Not regulated.

14.4. Packing group

PG: Not regulated.

14.5. Environmental hazards

Marine pollutant: Not regulated.

14.6. Special precautions for user

Special precautions: Not regulated.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk: -



Marine

SAFETY DATA SHEET

Product name:	GulfSea Gear Oil 68, 100, 150, 220, 320 460, 680	Page:	9/9
Supersedes date:	2019-11-18	Revision:	2019-11-18
Product No.:		SDS-ID:	HK-EN/1.0

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulation: Singapore Standard SS 586: Part 2 : 2014; Globally harmonised system of classification and labelling of chemicals - Singapore's adaptations. Guidelines on prevention and control of chemical hazard. Singapore Standard SS 586: Part 3 : 2014; Preparation of safety data sheets (SDS).

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Handling of used oils:

Protect health - avoid prolonged and repeated skin contact. Wash with soap and water. Protect the environment - do not pollute drains, water courses or the soil. Contact your local authority for any used oil disposal instructions.

Abbreviations and acronyms used in the safety data sheet: PBT = Persistent, Bioaccumulative and Toxic. vPvB = very Persistent and very Bioaccumulative.

Additional information: Classification according to Singapore Standard SS 586: Part 2 : 2014: Calculation method.

Wording of H-statements:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature.
