



OXYGEN

Wilhelmsen Ships Service AS

Part Number: 905075 - 905034

Version No: 4.7

Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878)

Issue Date: 05/03/2021 Print Date: 09/11/2023 L.REACH.NOR.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

Product name	OXYGEN
Chemical Name	oxygen
Synonyms	905075, O5, 905034, O40
Proper shipping name	OXYGEN, COMPRESSED
Chemical formula	Not Applicable
Other means of identification	905075 - 905034, 905034, 905075

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions.
Uses advised against	No specific uses advised against are identified.

1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Wilhelmsen Ships Service AS	Outback (M)SDS portal: http://jr.chemwatch.net /outb/account/autologin?login=wilhelmsen	Wilhelmsen Ships Service AS* Central Warehouse
Address	Strandveien 20 Lysaker 1366 Norway	Use our Outback portal to obtain our (M)SDSs in other languages and/or format For questions relating to our SDSs please use Email: WSS.GLOBAL.SDSINFO@wilhelmsen.comNorway	Willem Barentszstraat 50 Rotterdam Netherlands
Telephone	+47 67 58 40 00	Not Available	+31 10 4877 777
Fax	Not Available	Not Available	Not Available
Website	http://www.wilhelmsen.com/	http://www.wilhelmsen.com	http://www.wilhelmsen.com
Email	wss.norway.cs@wilhelmsen.com	wss.global.sdsinfo@wilhelmsen.com	wss.rotterdam@wilhelmsen.com

Registered company name	Nilhelmsen Ships Service AS* Central Warehouse	
Address	Willem Barentszstraat 50 Rotterdam Netherlands	
Telephone	+31 10 4877 777	
Fax	Not Available	
Website	http://www.wilhelmsen.com	
Email	wss.rotterdam@wilhelmsen.com	

1.4. Emergency telephone number

Association / Organisation	Giftinformasjonssentralen - 24 timer	24hrs - Chemwatch	Dutch nat. poison centre
----------------------------	--------------------------------------	-------------------	--------------------------

Page 2 of 13

OXYGEN

Issue Date: 05/03/2021 Print Date: 09/11/2023

Emergency telephone numbers	+47 22591300		+31-10-4877700	+ 31 88 7558561
Other emergency telephone numbers	+31-10-4877700		+31-10-4877700	+ 31 10 4877700
Association / Organisation	Dutch nat. poison centre CHEMW		VATCH EMERGENCY RESPONS	SE (24/7)

Association / Organisation	Dutch nat. poison centre	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	+ 31 30 274 88 88	+47 23 25 25 84
Other emergency telephone numbers	+ 31-10-4877700	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

Considered a hazardous mixture according to Reg. (EC) No 1272/2008 and their amendments. Classified as Dangerous Goods for transport purposes.

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments [1]	H280 - Gases Under Pressure (Compressed Gas), H270 - Oxidizing Gases Category 1
Legend:	1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

2.2. Label elements

Hazard pictogram(s)





Signal word

Danger

Hazard statement(s)

H280	Contains gas under pressure; may explode if heated.
H270	May cause or intensify fire; oxidiser.

Supplementary statement(s)

EUH044 Risk of explosion if heated under confinement.

CLP classification (additional)

Not Applicable

Precautionary statement(s) Prevention

	•
P220	Keep away from clothing and other combustible materials.
P244	Keep valves and fittings free from oil and grease.

Precautionary statement(s) Response

	<u> </u>
P370+P376	In case of fire: Stop leak if safe to do so.

Precautionary statement(s) Storage

P410+P403 P	Protect from sunlight. Store in a well-ventilated place.
--------------------	--

Part Number: 905075 - 905034

Version No: 4.7

Not Applicable

2.3. Other hazards

Inhalation may produce health damage*.

Cumulative effects may result following exposure*.

May produce discomfort of the respiratory system and skin*.

May be harmful to the foetus/ embryo*.

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 Composition / information on ingredients

3.1.Substances

See 'Composition on ingredients' in Section 3.2

3.2.Mixtures

1. CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
1. 7782-44-7. 2.231-956-9 3.008-001-00-8 4.Not Available	>99	oxygen	Oxidizing Gases Category 1, Gases Under Pressure (Compressed Gas); H270, H280, EUH044 [1]	Not Available	Not Available
Legend:	Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VII; 3. Classification drawn from Regulation (EU) No				3. Classification drawn from

SECTION 4 First aid measures

4.1. Description of first aid measures

Eye Contact

- If product comes in contact with eyes remove the patient from gas source or contaminated area.
- ▶ Take the patient to the nearest eye wash, shower or other source of clean water.
- Open the eyelid(s) wide to allow the material to evaporate.
- Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and tilt the head back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run out of the outer corners.
- The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the eyes to prevent further damage.
- Fensure that the patient looks up, and side to side as the eye is rinsed in order to better reach all parts of the eye(s)
- ► Transport to hospital or doctor.
- Feven when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur.
- If the patient cannot tolerate light, protect the eyes with a clean, loosely tied bandage.
- ▶ Ensure verbal communication and physical contact with the patient.

DO NOT allow the patient to rub the eyes

DO NOT allow the patient to tightly shut the eyes

DO NOT introduce oil or ointment into the eye(s) without medical advice

DO NOT use hot or tepid water.

Skin Contact

Inhalation

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- ► Seek medical attention in event of irritation.
- Following exposure to gas, remove the patient from the gas source or contaminated area.
- NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may be required to assure the safety of the rescuer.
- Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating first aid procedures.
- If the patient is not breathing spontaneously, administer rescue breathing.
- If the patient does not have a pulse, administer CPR.
- If medical oxygen and appropriately trained personnel are available, administer 100% oxygen.
- Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Control Centre for further instruction.
- ▶ Keep the patient warm, comfortable and at rest while awaiting medical care.
- MONITOR THE BREATHING AND PULSE, CONTINUOUSLY.

 Part Number: 905075 - 905034
 Page 4 of 13
 Issue Date: 05/03/2021

 Version No: 4.7
 Print Date: 09/11/2023

OXYGEN

	 Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask as trained) or CPR if necessary.
Ingestion	Not considered a normal route of entry.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

For gas exposures:
BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.

.....

ADVANCED TREATMENT

.....

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ► Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

Toxic myocarditis may follow ingestion of oxidizing agents such as peroxides.

BASIC TREATMENT

Establish a patent airway with suction where necessary.

- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- ► Anticipate seizures .
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- DO NOT attempt neutralisation as exothermic reaction may occur.
- ▶ Skin burns should be covered with dry, sterile bandages, following decontamination.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Figure 3. Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ► Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Firefighting measures

5.1. Extinguishing media

FOR SMALL FIRE:

- ▶ USE FLOODING QUANTITIES OF WATER.
- ▶ DO NOT use dry chemical, CO2, foam or halogenated-type extinguishers.

Part Number: 905075 - 905034

Version No: 4.7

Page **5** of **13**

OXYGEN

Issue Date: **05/03/2021**Print Date: **09/11/2023**

Flood fire area with water from a protected position

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid storage with reducing agents.

5.3. Advice for firefighters

olor / tavioo lor ill oligintor	~
Fire Fighting	GENERAL Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus and protective gloves. Fight fire from a safe distance, with adequate cover.
Fire/Explosion Hazard	Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. The material may provide sufficient oxygen to make the fire fierce and self sustaining. Smothering action may not be effective for established fire. Intense heat may cause spontaneous decomposition (detonation). Vented gas is more dense than air and may collect in pits, basements.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills	 Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used. DO NOT enter confined spaces where gas may have accumulated.
Major Spills	 Clear area of all unprotected personnel and move upwind. Alert Emergency Authority and advise them of the location and nature of hazard. Wear breathing apparatus and protective gloves. Remove leaking cylinders to a safe place. Fit vent pipes. Release pressure under safe, controlled conditions Burn issuing gas at vent pipes. DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

7.1. Precautions for safe	nandling
Safe handling	 Consider use in closed pressurised systems, fitted with temperature, pressure and safety relief valves which are vented for safe dispersal. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature The tubing network design connecting gas cylinders to the delivery system should include appropriate pressure indicators and vacuum or suction lines. Fully-welded types of pressure gauges, where the bourdon tube sensing element is welded to the gauge body, are recommended. DO NOT transfer gas from one cylinder to another.
Fire and explosion protection	See section 5
Other information	 Cylinders should be stored in a purpose-built compound with good ventilation, preferably in the open. Such compounds should be sited and built in accordance with statutory requirements. The storage compound should be kept clear and access restricted to authorised personnel only.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container	 Cylinder: Ensure the use of equipment rated for cylinder pressure. Ensure the use of compatible materials of construction. Valve protection cap to be in place until cylinder is secured, connected.
--------------------	---

Page 6 of 13

Version No: 4.7

Part Number: 905075 - 905034

OXYGEN

Issue Date: **05/03/2021**Print Date: **09/11/2023**

Oxygen:

- is a powerful oxidiser
- is non-flammable bur may initiate fire or explosions, or enhance the combustibility or oxidation rate of materials that were non-combustible in air
- at high concentrations (above 24%) will promote or support and accelerate the combustion of combustible and flammable materials; noncombustible materials such as steel and other metals will burn in pure oxygen.
- reacts exothermically with many materials
- reacts explosively with phosphine, hydrazine, hydrogen sulfide, ethers, alcohols and hydrocarbons
- reacts violently with reducing agents and all easily oxidisable materials; contact may cause fire/ explosion

NOTE: the heat of water will vigorously vapourise liquid oxygen.

The low temperature may cause brittleness on contact with some materials Keep away from clothing, lubricants, greases, elastic polymers and rubbers.

Storage incompatibility

- Inorganic reducing agents react with oxidizing agents to generate heat and products that may be flammable, combustible, or otherwise reactive. Their reactions with oxidizing agents may be violent.
- Incidents involving interaction of active oxidants and reducing agents, either by design or accident, are usually very energetic and examples of so-called redox reactions.
- · Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous
- ► Avoid storage with reducing agents.
- Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances
- Inorganic peroxy compounds are potent oxidisers that pose fire or explosive hazards when in contact with ordinary combustible materials.
- Inorganic peroxides react with organic compounds to generate organic peroxide and hydroperoxide products that react violently with reducing agents.
- Inorganic oxidising agents can react with reducing agents to generate heat and products that may be gaseous (causing pressurization of closed containers).

Hazard categories in accordance with Regulation (EC) No 1272/2008

P4: Oxidising Gases

Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of

P4 Lower- / Upper-tier requirements: 50 / 200















- X Must not be stored together
- May be stored together with specific preventions
- + May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

7.3. Specific end use(s)

See section 1.2

SECTION 8 Exposure controls / personal protection

8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment	
Not Available	Not Available	Not Available	

^{*} Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

OXYGEN

Issue Date: **05/03/2021**Print Date: **09/11/2023**

Not Applicable

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
OXYGEN	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH	
oxygen	Not Available	Not Available	

MATERIAL DATA

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more.

For oxygen:

No exposure standards available

NOTE: Detector tubes for oxygen, measuring in excess of 5 vol%, are commercially available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

8.2.2. Individual protection measures, such as personal protective equipment







Eye and face protection

- Safety glasses with side shields.
- Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.

Skin protection

See Hand protection below

Hands/feet protection

When handling sealed and suitably insulated cylinders wear cloth or leather gloves.

Body protection

See Other protection below

- Overalls.
- ► PVC Apron.

Other protection

- ▶ PVC protective suit may be required if exposure severe.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).
- ▶ Non sparking safety or conductive footwear should be considered.

Respiratory protection

- Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

8.2.3. Environmental exposure controls

See section 12

SECTION 9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Not Available			
Physical state	Compressed Gas	Relative density (Water =	Not Available	
Odour	Not Available	Partition coefficient n-octanol / water	Not Available	
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available	

OXYGEN

Decomposition Not Available Not Available pH (as supplied) temperature (°C) Melting point / freezing -218 Viscosity (cSt) Not Available point (°C) Initial boiling point and -183 Molecular weight (g/mol) Not Available boiling range (°C) Flash point (°C) Not Available Not Available **Taste Evaporation rate** Not Available BuAC = 1 **Explosive properties** Not Available Flammability Not Available Oxidising properties Not Available Surface Tension (dyn/cm Upper Explosive Limit (%) Not Available Not Available or mN/m) Lower Explosive Limit (%) Not Available **Volatile Component (%vol)** Not Available Vapour pressure (kPa) Not Available Gas group Not Available Solubility in water Partly miscible pH as a solution (1%) Not Available Vapour density (Air = 1) VOC g/L Not Available 1.1 **Nanoform Particle Nanoform Solubility** Not Available Not Available Characteristics

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

Particle Size

Not Available

10.1.Reactivity	See section 7.2
10.2. Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhaled	Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure. Symptoms of asphyxia (suffocation) may include headache, dizziness, shortness of breath, muscular weakness, drowsiness and ringing in the ears. If the asphyxia is allowed to progress, there may be nausea and vomiting, further physical weakness and unconsciousness and, finally, convulsions, coma and death. Significant concentrations of the non-toxic gas reduce the oxygen level in the air. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.
Ingestion	Overexposure is unlikely in this form. Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the

Issue Date: 05/03/2021

Print Date: 09/11/2023

	exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
Еуе	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). Direct contact with the eye may not cause irritation because of the extreme volatility of the gas; however concentrated atmospheres may produce irritation after brief exposures		
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. Principal route of occupational exposure to the gas is by inhalation.		
	TOVICITY		PRITATION
OXYGEN	TOXICITY Not Available		RRITATION Not Available

OVVOEN	TOXICITY	IRRITATION
OXYGEN	Not Available	Not Available
	TOVICITY	IDDITATION
ovygen	TOXICITY	IRRITATION
oxygen	Not Available	Not Available
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

OXYGEN	Inhalation (human) TCLo: 100pph (100%)/14hNil reported No significant acute toxicological data identified in literature search.		
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend: X − Data either not available or does not fill the criteria for classification

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

11.2.2. Other information

See Section 11.1

SECTION 12 Ecological information

12.1. Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
OXYGEN	Not Available	Not Available	Not Available	Not Available	Not Available
oxygen	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	4. US EPA, E	m 1. IUCLID Toxicity Data 2. Europe ECH, cotox database - Aquatic Toxicity Data 5. tion Data 7. METI (Japan) - Bioconcentrat	ECETOC Aquatic Hazard Assessn		

OXYGEN

Issue Date: **05/03/2021**Print Date: **09/11/2023**

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

12.5. Results of PBT and vPvB assessment

	P	В	Т
Relevant available data	Not Available	Not Available	Not Available
PBT	×	×	×
vPvB	×	×	×
PBT Criteria fulfilled?			No
vPvB			No

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods

Product / Packaging disposal	Place leaking oxygen cylinder(s) in a remote place away from combustibles and allow the gas to slowly bleed off to the atmosphere. To increase the rate of controlled evaporation of spilled or leaking oxygen (when desired), spray the spill with large amounts of water. (This may generate a fog and reduce visibility). Evaporate residue at an approved site. Return empty containers to supplier. If containers are marked non-returnable establish means of disposal with manufacturer prior to purchase.
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 Transport information

Labels Required



Land transport (ADR-RID)

14.1. UN number or ID number	1072
14.2. UN proper shipping name	OXYGEN, COMPRESSED

OXYGEN

Issue Date: **05/03/2021**Print Date: **09/11/2023**

14.3.	Transport hazard class(es)	Class	2.2	
		Subsidiary Hazard	5.1	
14.4.	Packing group	Not Applicable		
14.5.	Environmental hazard	Not Applicable		
	Special precautions for user	Hazard identification	(Kemler)	25
		Classification code		10
14.6.		Hazard Label		2.2 +5.1
		Special provisions		355 655 662
		Limited quantity		0
		Tunnel Restriction C	ode	E

Air transport (ICAO-IATA / DGR)

14.1. UN number	1072			
14.2. UN proper shipping name	Oxygen, compressed			
	ICAO/IATA Class 2.2			
14.3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	5.1		
ciass(es)	ERG Code 2X			
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Not Applicable			
	Special provisions		A175 A302	
	Cargo Only Packing Instructions	200		
	Cargo Only Maximum Qty / Pack	150 kg		
14.6. Special precautions for user	Passenger and Cargo Packing In	200		
101 4001	Passenger and Cargo Maximum Qty / Pack		75 kg	
	Passenger and Cargo Limited Qu	Forbidden		
	Passenger and Cargo Limited Ma	aximum Qty / Pack	Forbidden	

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1072				
14.2. UN proper shipping name	OXYGEN, COMPRES	OXYGEN, COMPRESSED			
14.3. Transport hazard class(es)	IMDG Class IMDG Subsidiary Ha	2.2 zard 5.1			
14.4. Packing group	Not Applicable				
14.5 Environmental hazard	Not Applicable				
14.6. Special precautions for user	EMS Number Special provisions Limited Quantities	F-C, S-W 355 0			

Inland waterways transport (ADN)

14.1. UN number	072				
14.2. UN proper shipping name	OXYGEN, COMPRESSED				
14.3. Transport hazard class(es)	2.2 5.1				
14.4. Packing group Not Applicable					

OXYGEN

Issue Date: **05/03/2021**Print Date: **09/11/2023**

14.5. Environmental hazard	Not Applicable		
	Classification code	10	
	Special provisions	355; 655; 662	
14.6. Special precautions for user	Limited quantity	0	
Tor user	Equipment required	PP	
	Fire cones number	0	

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
oxygen	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
oxygen	Not Available

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

oxygen is found on the following regulatory lists

Europe EC Inventory

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable -: Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category	P4

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (oxygen)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (oxygen)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes

 Part Number: 905075 - 905034
 Page 13 of 13
 Issue Date: 05/03/2021

 Version No: 4.7
 OXYGEN
 Print Date: 09/11/2023

Status
Yes
Yes
Yes = All CAS declared ingredients are on the inventory
No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	05/03/2021
Initial Date	14/09/2017

CONTACT POINT

- For quotations contact your local Customer Services - http://wssdirectory.wilhelmsen.com/#/customerservices - - Responsible for safety data sheet Wilhelmsen Ships Service AS - Prepared by: Compliance Manager, - Email: Email: wss.global.sdsinfo@wilhelmsen.com - Telephone: Tel.: +47 67584000

Full text Risk and Hazard codes

SDS Version Summary

Version	Date of Update	Sections Updated	
3.7	05/03/2021	Toxicological information - Acute Health (inhaled), Toxicological information - Chronic Health, Ecological Information - Environmental, Composition / information on ingredients - Ingredients, Handling and storage - Storage (storage incompatibility)	

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Powered by AuthorITe, from Chemwatch.