



SAFETY, HEALTH, ENVIRONMENT AND QUALITY MANAGEMENT SYSTEM

PORT OF CALL HISTORY

REPORTING FORMS MANUAL

Form : 1.3.1B
Date : 02/June/2017
Rev : 1.0
App By : BMM**Port Feedback**

Ship Name	IVS PHINDA
Port	PICTON, NEW ZEALAND
Terminal & Berth No.	WAIMAHARA BERTH

Port Details

Anchorage approach	West of Mabel Island (Mud)
Min. depth at anchorage/Channel	MIN. DEPTH ANCHORAGE: 20 - 27m / CHANNEL: 10.7m
Pilot performance/Tugs condition	Good performance / tugs in good condition
Other information	Current:

Berth Details

Berth Type	Concrete Construction Wharf
Minimum depth at Berth/approach/UKC concern	MIN. DEPTH AT BERTH: 15.3m, Starboard side alongside, MIN. UKC: 1.0m
Mooring arrangement	4 Head lines & Stern lines with 2 Fwd & Back Spring Lines
Berth Restrictions	No crew allowed while under cargo operation, Complete PPE required while at berth with visible vest
Berth condition/fendering etc	Fully concrete berth with log fendering attached on side.
Other information (fendering etc)	BERTH Density: 1.025 g/cm3

Cargo Operation

Manifold connections	Ships Crane with 3 gangs, slings and log picker for loading.
Terminal courtsey/co-operation	Authorities and terminal personnel are cooperated.
Safety standard	Strict implementation of ISPS & PPE requirements.
Other information (booster pumps etc)	No walking is permitted whilst in port.

Additional information

Authorities(Custom/immig./health)	AGENT/ CUSTOMS/ IMMIG./ QUARANTINE ONBOARD
Security (Stowaways/theft threats)	SECURTY LEVEL 1
Spares/Stores/FW supply	Spares, Stores, FW Supply available to be arrange thru agent.
Crew change/Shore leave	Shore leave possible with shuttle van service to town.
General comments	Gangway & Mooring lines should be tended regularly. Adjusted & tight due to tides.
Recommendations	Observe safe working practices whilst handling mooring ropes.

Master's Name / Date	CAPT. P.M. MONTWILL / 14 NOV. 2019
----------------------	------------------------------------