	<p>HEALTH, SAFETY, ENVIRONMENT AND QUALITY MANAGEMENT SYSTEM</p> <p><b>60.0 NEW REQUIREMENTS ON MAINTENANCE OF LSA</b></p> <p>ON THE JOB TRAINING</p>	<p>OJT : 060  Page : 1 of 2  Date : 07-Nov-25  Rev : 10.1  Appr : DPA</p>
--	---	---


VESSEL: \_\_\_\_\_

DATE: \_\_\_\_\_

### **Details of training: New Requirements on Maintenance of LSA**

Effective from 01 Jan 2020: as per MSC. 402(96)

- Weekly and monthly inspections shall be conducted by shipboard personnel (3O/3EO or an officer as assigned by master) **under the direction of a senior officer (CO/2EO)**.
- Any inspection, maintenance, thorough examination, operational testing, overhaul and repair shall be carried out according to the maintenance manuals and associated technical documentation developed by the manufacturer.
- Annual thorough examinations and operational tests, five-year thorough examination, overload operational tests shall be conducted by certified personnel from either the manufacturer or an authorized service provider.
- Whenever work required by an authorized service provider is carried out, ensure the following is received:
  - Service report
  - Personnel certificate
  - IACS Approved Service Suppliers (AoSS) certificate proving compliance for the make and type of the on-board equipment
- All reports and checklists must be completed and signed by the person carrying out the inspection and maintenance work and countersigned by the Company's representative or ship's Master.
- If attending service personnel do not have a certificate stating that he/she is approved to perform service of the life-saving appliances on board, Class may not accept the service carried out.
- Records of maintenance, thorough examination, operational testing, overhaul and repair shall be updated and filed on board the ship for the service life of the equipment as per the company filing system.
- The setting and maintenance of release gear are critical operations with regard to maintaining the safe operation of lifeboats (including free-fall lifeboats), rescue boats, fast rescue boats and davit launched life rafts. Utmost care shall be taken when carrying out all inspection and maintenance operations on the equipment.
- No maintenance or adjustment of the release gear shall be undertaken while the hooks are under load.
- **Ship staff shall ensure that a statement confirming that lifeboat arrangements remain fit for purpose is promptly issued by the manufacturer or authorized service provider that conducted the maintenance work. The statement must include any relevant, valid documents of certification and authorization.**
- The relevant maintenance manuals and associated technical documentation developed by the manufacturer must be kept up-to-date and available on board.

	<p align="center"><i>HEALTH, SAFETY, ENVIRONMENT AND QUALITY MANAGEMENT SYSTEM</i></p> <p align="center"><b>60.0 NEW REQUIREMENTS ON MAINTENANCE OF LSA</b></p> <p align="center"><i>ON THE JOB TRAINING</i></p>	<p>OJT : 060  Page : 2 of 2  Date : 07-Nov-25  Rev : 10.1  Appr : DPA</p>
--	--	---

**The above has been read and understood :**

CO: \_\_\_\_\_

2O: \_\_\_\_\_

3O: \_\_\_\_\_

D/C \_\_\_\_\_

CEO \_\_\_\_\_

2EO \_\_\_\_\_

3EO \_\_\_\_\_

4EO \_\_\_\_\_

E/C \_\_\_\_\_

Verified by: Master \_\_\_\_\_